

running machine: **locomotion® 190/65-3p E med**
with therapist seats, foot rests and adjustable handrails
optional wheelchair ramp available at extra charge

manufacturer: h/p/cosmos sports & medical gmbh / Germany

order number: cos30024va02

applications: endurance training walking and running,
stress device for performance testing,
gait analysis & gait training

control: via integrated interface and coscom protocol or via para
control PC software or via remote control only; MCU5
(WITHOUT UserTerminal, no displays, no keyboard)

running surface: L: 190 cm (6ft 2.8") B: 65 cm (2ft 1.6")
special sizes available at extra charge
access height: 23 cm (9.06")
- shock load reduction for the joints
- running belt with slip resistant surface
- reinforced running belt with profiled surface, 5 mm thick
- max. permissible load: 200 kg (440 lbs)
- optional 300 kg (660 lbs) at extra charge

speed range: 0...25.0 km/h (0...6.9 m/s) (0...15.5 mph)
special speed available at extra charge:
0...10 km/h (0...6.2 mph)

acceleration: 7 acceleration / deceleration levels
between 131 s and 3 s from 0 to max. or from max. to 0;
equals 0.053... 2.31 m/s²
programmable via para control PC software

elevation: -25.0 %...+25.0 % (-14.0°...014.0°) motorized adjustment,
(up to -25 % when using reverse belt rotation)

running direction: switch for reversing running belt direction as standard,
max. permissible reverse speed 5 km/h (3.1 mph) if no
safety-harness with fall-stop prevention system is used.

motor system: 4.3 kW (5.8 PS) 3-phase AC motor, maintenance free and
brushless; 20 years warranty on main drive motor.

electr. motor brake: Prevents almost all movement of running belt
when speed is set to 0 km/h caused by elevation/gravity or
when mounting or dismounting the treadmill.

power transmission: frequency inverter, poly-V-belt, very quiet operation

safety systems: CE0123; medical device directive 93/42/EEC +
2007/47/EC; MDD; machinery directive 2006/42/EC;
IEC 60601-1; EN 60601-1-2 (EMC approved);
EN 60601-1-6; EN 62304; EN 62353; ISO 20957-1;
EN 957-6; EN 14971; EN ISO 13485;
emergency-off safety stop switch (mushroom push button
for drive system power-off); emergency stop switch
(safety lanyard with actuator, pull cord and clip);
potential equalization bolt;
transformer for potential-isolation from the mains.

degree of protection: appliance class I (Ⓛ) / type B (⚡) / IP 20

classification: medical device risk class IIb according to MDD,
active therapeutic medical device and
active diagnostic medical device

usage class: S, I according to ISO 20957-1

accuracy class: A (high accuracy) according to EN 957-6

earth leakage current < 0.2 mA

ambient condition: temperature: +10...+40 °C (-30...+50 °C on request)
humidity: 30...70 % (up to 100 % on request)
air pressure: 700...1060 hPa; 3,000 m (~10,000 ft) max.
altitude without pressurization

data (resolutions): via integrated interface and coscom;
(via PC software) 6 LCD displays, 4 LEDs for operation modes,
20 LEDs for display of units & profile no, steps, etc.
speed (0.1 km/h or m/s or m/min or mph), time (00:00) in
hours, minutes & seconds, elevation (0.1 % or degrees)
distance (1 m...999.9 km or miles), METS (1 MET)
program step/number, energy (1 kJ/kcal), fitness index (1)
power (1 Watt), heart rate (1 bpm / beat per minute)

heart rate monitoring: optional at extra charge (Cardio-mode is blocked)

digital interface: 2 x RS 232 com1 & com2 with 9600 bps: incl. PC-protocol,
h/p/cosmos coscom® & printer protocol serial.

option extra charge: USB-RS232-converter;
com3 with 115200 bps;

programs: 42 programs / profiles
- 6 exercise profiles (scalable, more than 100 variations)
- 28 test profiles (UKK 2 km Walktest, Bruce, Graded test, Naughton, Ellestad, Gardner, Conconi, Ramp, etc.)
- 8 free definable programs with 40 program steps each

PC software (incl.): h/p/cosmos para control® for display & remote control;
h/p/cosmos para graphics® for recording & visualization;
including 2 x RS232 interface cable
(1 x 5 m (16 ft 4.85")), 1 x 10 m (32 ft 9.70")).

PC software: h/p/cosmos para analysis® & para motion®.
(extra charge) PC software for monitoring, recording & motion analysis.

accessory (incl.): external emergency stop & remote control keyboard
magnetic, user manual, service box, special oil,
5 m (16ft 4.85") PE potential equalization cable

colour of frame: pure white RAL 9010 (powder coated)

handrails: steel tube handrails Ø 40 mm on both sides;
gas-spring support and scales, adjustment in
height 70...115 cm and width 46...117 cm,
with 2 telescope bar extensions
L: 55 cm 25mm Ø for wheelchair users

voltage supply: 400 Volt AC 3~/N/PE 50/60 Hz 15-16A fuse;
dedicated circuit, line and protection;

size of frame: L: 250 cm (8ft 2.4") B: 115 cm (3ft 9.2")
H: 145 cm (4ft 9.1")
max. B: 155 cm (5ft 1.02") incl. 2 therapist seats
max. L: 375 cm (12ft 3.64") incl. optional wheelchair ramp

net weight: device approx. 600 kg (1323 lbs)

gross weight: device approx. 700...800 kg (1543...1763 lbs)

Optionally available at extra charge are special frame colours, other handrail designs, special voltage supply and other options and accessories.
Weight and package specifications can deviate according to options, accessories packing and way of transport. E&OE. Subject to alterations without prior notice.
Please consider the natural and physical performance limitations of the single phase 230 volt power supply. The single phase 230 volt power supply is sufficient up to normal fitness or therapy applications. For all special high performance applications (speed running, controlled jump-ons, sidesteps, heavy subjects at higher speed, extreme elevations, etc.), we recommended models with a 3-phase, 3x400 volt power supply (for example model h/p/cosmos quasar med 3p, pulsar 3p, venus or saturn).

Warning! Installation, commissioning, instruction, maintenance and repair work only to be conducted by h/p/cosmos trained and authorized personnel. For treadmills with oversized deck (width >65cm), for children, special applications, without sufficient safety space behind the treadmill, for subjects and / or patients with health or other limitations (e.g. visual impairment, etc.), for running at high speed and / or for all individuals, where a fall triggers a dangerous risk of injury or death (e.g. newly operated hip patients, invasive probes, etc.), a fall prevention system is obligatory (e.g. safety arch with chest belt and harness or a weight support system). For more information see the instructions for use. Safety space behind the treadmill: min. L: 2 m (6ft 6.74") x treadmill width. Children are only allowed to be on the treadmill, if under permanent supervision and secured by a fall prevention system.